

# WISA®-Oil

WISA-Oil is a concrete forming panel which is oiled and edge-sealed in controlled factory conditions. The panel is suitable for wall and floor castings with low visual requirements, especially for dead mold castings.

## Base board

Spruce plywood

## Bonding

Weather resistant bonding according to EN 314-2/class 3.

## Panel surfaces

Face and reverse sides are oil treated with a release agent.  
Surface quality II / III

## Thicknesses

18 mm (17.1 – 18.1 mm) 7-ply

21 mm (20 – 20.9 mm) 7-ply

## Weights

18 mm abt. 8.3 kg/m<sup>2</sup>

21 mm abt. 9.7 kg/m<sup>2</sup>

## Dimensions

2440 x 1200 mm

2400 x 1200 mm

2500 x 1250 mm

Other dimensions on special request

FRITZOE  
ENGROS





**Standard size tolerances:**

< 1000 mm +/- 1 mm

1000 – 2000 mm +/- 2 mm

2000 – 3000 mm +/- 3 mm

Squareness tolerance: +/- 1 mm / 1000 mm

**Edge-sealing**

The edges of WISA-Oil are protected with edge paint to help reduce moisture penetration. If panels are cut or drilled all cut edges and holes must be painted immediately with a suitable paint.

**Environment**

WISA wood products are manufactured from wood raw material supplied according to the principles of sustainable forestry. [www.pefc.com](http://www.pefc.com)

Production of plywood and veneer is much less energy intensive compared to other products for the same end use areas. Therefore all WISA wood products have a low carbon footprint. Wood products can also replace fossil fuels in energy production at the end of their life cycle. [www.wisaplywood.com/environment](http://www.wisaplywood.com/environment)

**FRITZOE**  
**ENGROS**

