

## Mutter for formstag



Mutter for formstag med DW gjenge. Leveres med ubehandlet overflate.

### Lagerprogram:

DW 15x50  
DW 20x70  
DW 26,5x80

### Teknisk informasjon:

DW 15x50: Nøkkelvidde 30 mm. Lengde 50mm.  
DW 20x70: Nøkkelvidde 36 mm. Lengde 70mm.  
DW 26,5x70: Nøkkelvidde 46 mm. Lengde 80mm.

Dimensjonert for minimum 100 kN (statisk last)  
Dimensjonert for minimum 160 kN (statisk last)  
Dimensjonert for minimum 250 kN (statisk last)

Materialet er ikke sveisbart under normale forhold på byggeplass. Sveising krever kontrollert oppvarming og nedkjøling for å unngå sprøbrudd.

### Tilbehør:

Formstag      DW 15/20/26,5  
Skjøtemutter   DW 15/20/26,5

## Nut for tie bars



Hex Nut for tie bars with DW thread. Delivered with plain surface

### Stock programme:

DW 15x50  
DW 20x70  
DW 26,5x80

### Technical information:

DW15: SW 30mm. Length 50 mm.	Minimum load test values: 100 kN (Static load)
DW20: SW 36mm. Length 70 mm.	Minimum load test values: 160 kN (Static load)
DW26,5: SW 46mm. Length 80 mm.	Minimum load test values: 250 kN (Static load)

Material is not suited for welding under normal conditions on site. Welding requires special procedure (WPS) and trained welders.

### Accessories:

Tie rod DW 15/20/26,5  
Coupler DW 15/20/26,5