

# NorGeoSpec 2012 Product Certificate



Certificate no.: NGS-50060

Manufacturer: THRACE NG

Raw material: PP

Date: 03.02.2017

Product: 140NW

Function: Separation and Filtration

Valid until: 02.02.2019

Product Type: GTX-N

## Quality Product Certification Separation and Filtration

Characteristic		Standard	Unit	Declared value	Max. tolerance	Certification value
Mass per unit area		EN ISO 9864	g/m <sup>2</sup>	132	± 13	<b>119 - 145</b>
Mechanical tests						
Tensile strength	MD	EN ISO 10319	kN/m	11.00	- 1.00	<b>10.00</b>
	CMD	EN ISO 10319	kN/m	11.00	- 1.00	
Elongation at max. load	MD	EN ISO 10319	%	40.0	- 8.0	<b>32.0</b>
	CMD	EN ISO 10319	%	40.0	- 8.0	
Static puncture test		EN ISO 12236	kN	1.650	- 0.150	<b>1.500</b>
Dynamic perforation resistance		EN ISO 13433	mm	30	6	<b>36</b>
Energy index		NorGeoSpec 2012	kN/m	2.1	0.0	<b>2.1</b>
Hydraulic tests						
Velocity index		EN ISO 11058	m/s	0.090	- 0.027	<b>0.063</b>
Characteristic opening size		EN ISO 12956	µm	100	± 30.0	<b>70 - 130</b>
Durability (Declared value)						
Service life			years	25		

### Quality Product Specification

Separation and Filtration

Application profile: **2**

Issued by

Christian Recker, NorGeoSpec project manager

Approved by

Arnstein Watn, Head of the Technical committee



The products are regularly audited and tested to verify that the characteristics fulfil the NorGeoSpec requirements.  
Approved by the NorGeoSpec Technical committee: 03.02.2017